CERTIFICATE OF COMPLIANCE

Certificate Number Report Reference Issue Date 20130830-E181974 E181974-20130830 2013-AUGUST-30

Issued to: TEXAS INSTRUMENTS TUCSON CORP 5411 E WILLIAMS BLVD TUCSON AZ 85711

This is to certify that representative samples of

COMPONENT - NONOPTICAL ISOLATING DEVICES Single Protection Non-Optical Isolator, Models ISO7131, ISO7140, ISO7141, ISO7142. May be followed by any suffix.

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: Additional Information: UL 1577-Optical Isolators See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Recognized Component Mark should be considered as being covered by UL's Recognition and Follow-Up Service.

The UL Recognized Component Mark generally consists of the manufacturer's identification and catalog number, model number or other product designation as specified under "Marking" for the particular Recognition as published in the appropriate UL Directory. As a supplementary means of identifying products that have been produced under UL's Component Recognition Program, UL's Recognized Component Mark: **N**, may be used in conjunction with the required Recognized Marks. The Recognized Component Mark is required when specified in the UL Directory preceding the recognitions or under "Markings" for the individual recognitions.

Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for use as components of complete equipment submitted for investigation rather than for direct separate installation in the field. The final acceptance of the component is dependent upon its installation and use in complete equipment submitted to UL LLC.

Look for the UL Recognized Component Mark on the product.

Western R. Curry

William R. Carney, Director, North American Certification Programs UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus File E181974 Project 13CA26290

August 30, 2013

REPORT

on

COMPONENT - Non-Optical Isolating Devices - Component

Texas Instruments Tucson Corp Tucson, Arizona

Copyright $\ensuremath{\mathbb{C}}$ 2013 UL LLC

UL LLC authorizes the above named company to reproduce this Report only for purposes as described in the Conclusion. The Report should be reproduced in its entirety; however to protect confidential product information, the Construction Details Descriptive pages may be excluded.

File E181974	Vol. 5	Sec. 1	Page 1	Issued:	2013-08-30

DESCRIPTION

PRODUCT COVERED:

USR - Single Protection Non-Optical Isolator, Models ISO7131, ISO7140, ISO7141, ISO7142. May be followed by any suffix.

MAXIMUM RATINGS PER	CHANNEL (a	t 25°C	ambient)	(S):
---------------------	------------	--------	----------	------

				,	117				
	Current (mA)		Power (mW)		Isolation	Max	Max	Max	Max
Model	Transmitter	Receiver	Transmitter	Receiver	Voltage	Operating	Junction	Storage	Data
Model					at 60 sec	Ambient	Temp	Temp	Rate,
					Vrms	Temp (°C)	(°C)	(°C)	Mbps
ISO7131	0.00010	13	0.055	71.5	2500	125	150	150	50
ISO7140	0.00010	18	0.055	99	2500	125	150	150	50
ISO7141	0.00010	16	0.055	88	2500	125	150	150	50
ISO7142	0.00010	14	0.055	77	2500	125	150	150	50

(\$) - For ambient temperatures higher than 25°C and up to Tmoa, refer to manufacturer's specifications and/or thermal derating curve data for complete electrical ratings.

GENERAL:

These non-optical isolator devices consist of a transmitter coupled to a receiver. The transmitter and receiver are separated by an insulating barrier between capacitor plates. Internal chips are connected to lead frames that are molded into the enclosure.

TECHNICAL CONSIDERATIONS (NOT FOR FIELD REPRESENTATIVE'S USE):

Use - For use only in products where the acceptability of the combination is determined by UL LLC.

USR indicates this product was investigated under the UL Standard for Safety for Optical Isolators, UL 1577, Fourth Edition.

Conditions of Acceptability - Each device shall be reviewed with respect to the following conditions of acceptability:

- 1. The capability of the device to control a load has not been investigated.
- 2. These devices should be installed in a suitable end product enclosure.
- 3. The maximum junction temperature shall not be exceeded.
- 4. For single protection devices, the insulation to the case has not been evaluated. For double protection devices, the insulation to the case has been evaluated to the isolation voltage specified in the ratings table.
- 5. In addition to meeting single protection requirements, double protection optical isolators have also been investigated for use in up to 250 V, 50/60 Hz circuits in audio, video, and similar equipment in applications in which breakdown of the optical isolator may result in a risk of fire, electrical shock, or injury to persons.

CONSTRUCTION DETAILS:

General - The product shall be constructed in accordance with the following description. All dimensions are approximate, unless specified as "max" or "min".

Markings - As specified in the Section General.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265 Copyright © 2022, Texas Instruments Incorporated