



1 Startup


The photo below shows the output voltage startup waveform after the application of 6.5V in. The 10V output was loaded to 0A. (Vin is 5V/DIV, Vout is 2V/DIV, 10mS/DIV)




The photo below shows the output voltage startup waveform after the application of 6.5V in. The 10V output was loaded to 2A. (Vin is 5V/DIV, Vout is 2V/DIV, 10mS/DIV)



The photo below shows the output voltage startup waveform after the application of 16V in. The 10V output was loaded to 0A. (Vin is 5V/DIV, Vout is 2V/DIV, 10mS/DIV)




The photo below shows the output voltage startup waveform after the application of 16V in. The 10V output was loaded to 2A. (Vin is 5V/DIV, Vout is 2V/DIV, 10mS/DIV)




2 Efficiency


The converter efficiency is shown below for $V_{in} = 12V$ and $V_{out} = 10V$.



The converter efficiency is shown below for $V_{in} = 16V$ and $V_{out} = 10V$.




The converter efficiency is shown below for $V_{in} = 6.5V$ and $V_{out} = 10V$.




3 Output Ripple Voltage

The 10V output ripple voltage (AC coupled) is shown in the figure below. The image was taken with the output loaded to 2A. The input voltage is set to 6.5V. (50mV/DIV, 1uS/DIV)




The 10V output ripple voltage (AC coupled) is shown in the figure below. The image was taken with the output loaded to 2A. The input voltage is set to 16V. (50mV/DIV, 1uS/DIV)




4 Load Transients


The photo below shows the 10V output voltage (ac coupled) when the load current is stepped between 1A and 2A. $V_{in} = 12V$.
(500mV/DIV, 1A/DIV, 200uS/DIV)




The photo below shows the 10V output voltage (ac coupled) when the load current is stepped between 0.5A and 2A. $V_{in} = 12V$.
(500mV/DIV, 1A/DIV, 200uS/DIV)



The photo below shows the 10V output voltage (ac coupled) when the load current is stepped between 0.25A and 2A. $V_{in} = 12V$.
(500mV/DIV, 1A/DIV, 200uS/DIV)




The photo below shows the 10V output voltage (ac coupled) when the load current is stepped between 0A and 2A. $V_{in} = 12V$.
(1V/DIV, 1A/DIV, 200uS/DIV)




5 Switch Node Waveforms


The photo below shows the FET switching voltage for an input voltage of 6.5V and a 2A load.
(5V/DIV, 500nS/DIV)




The photo below shows the FET switching voltage for an input voltage of 12V and a 2A load.
(5V/DIV, 500nS/DIV)



The photo below shows the FET switching voltage for an input voltage of 16V and a 2A load.
(5V/DIV, 500nS/DIV)



The photo below shows the FET switching voltage for an input voltage of 16V and a 0.45A load.
The converter is operating in DCM. (5V/DIV, 500nS/DIV)



6 Loop Gain

The plot below shows the loop gain with the input voltage set to 6.5V and 16V with the output set to 2A.

Loop Gain (Vin = 6.5V)


BW: 12.3KHz

PM: 60 degrees

Loop Gain (Vin = 16V)

BW: 16.6KHz

PM: 68 degrees



The plot below shows the loop gain with the input voltage set to 6.5V and 16V with the output set to 0.5A.

Loop Gain (Vin = 6.5V)


BW: 11.5KHz

PM: 73 degrees

Loop Gain (Vin = 16V)


BW: 3.36KHz

PM: 74 degrees




7 Photo

The photo below shows the PMP20193 REVC assy.



8 Thermal Image

A thermal image is shown below operating at 12V input and 10V@2A output (room temp, no airflow).



IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (<https://www.ti.com/legal/termsofsale.html>) or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2021, Texas Instruments Incorporated