

- Install label in silkscreened box after final wash. Text shall be 8 pt font. Text shall be per Table 1
- These assemblies are ESD sensitive, ESD precautions shall be observed.
- These assemblies must be clean and free from flux and all contaminants. Use of no clean flux is not acceptable.
- These assemblies must comply with workmanship standards IPC-A-610 Class 2., unless otherwise specified.





TABLE 1

| Variant | Label text |
|---------|------------|
| 001     | UCC28720   |
| 002     | ChangeMe!  |

COMPONENTS MARKED 'DNP' SHOULD NOT BE POPULATED.  
ASSEMBLY VARIANT: -001

|                                  |                                  |                   |                                |
|----------------------------------|----------------------------------|-------------------|--------------------------------|
| PCB VIEWED FROM TOP SIDE         | BOARD #: PMP9517                 | REV: E1           | SVN REV: Not In VersionControl |
| IGNORE -> Top Overlay            |                                  |                   |                                |
| PLOT NAME = Top Assembly Drawing | GENERATED : 3/19/2014 8:55:55 AM | TEXAS INSTRUMENTS |                                |



COMPONENTS MARKED 'DNP' SHOULD NOT BE POPULATED.  
ASSEMBLY VARIANT: -001

|                                     |                                  |         |                                |
|-------------------------------------|----------------------------------|---------|--------------------------------|
| PCB VIEWED FROM BOTTOM SIDE         | BOARD #: PMP9517                 | REV: E1 | SUN REV: Not In VersionControl |
|                                     | IGNORE -> Bottom Overlay         |         |                                |
| PLOT NAME = Bottom Assembly Drawing | GENERATED : 3/19/2014 8:55:55 AM |         | TEXAS INSTRUMENTS              |