TLV522 デュアルNanoPower、500nA、RRIO CMOSオペアンプ

1 特長

- 比類のないコストパフォーマンス
- 広い電源電圧範囲: 1.7V～5.5V
- 低消費電流: 500nA
- 優れたオフセット電圧: 4mV (最大)
- 優れたTcVos: 1.5 µV/°C
- ゲイン帯域幅8kHz
- レール・ツー・レールの入出力(RRIO)
- ユニティ・ゲインで安定
- 低い入力バイアス電流: 1pA
- EMI強化
- 温度範囲-40°C～125°C
- 8ピンVSSOPパッケージ

2 アプリケーション

- 個人用の健康監視
- バッテリ・パック
- 太陽電池または環境発電システム
- PIR、煙、ガス、火災の検出システム
- バッテリ駆動のIOT (Internet of Things)デバイス
- リモート・センサ/ワイヤレス感知ノード
- ウェアラブル
- 血糖監視

3 概要

TLV522 500nAデュアルNanoPowerオペアンプは、TIのNanoPowerファミリのオペアンプの中でも最高のコストパフォーマンスを提供します。TLV522は、500nAの待機時消費電流から8kHzのゲイン帯域幅を提供するため、建造物の自動化やリモート感知ノードに使用されるバッテリ駆動のアプリケーションに最適です。CMOS入力ステージにより、I_{BIAS}が非常に低く、高インピーダンスのフォトダイオードや電荷感知アプリケーションなど、メガオーム・フィードバック抵抗トポロジで一般的に発生する誤差を低減できます。さらに、EMI保護が組み込まれているため、携帯電話、WiFi、ラジオ送信機、RFIDリーダーなどのソースから発生する不要なRF信号への感受性が低下しています。


TLV522は8ピンのVSSOP (MSOP)パッケージで提供され、-40°C～125°Cで動作します。

製品情報(1)

型番	パッケージ	本体サイズ(公称)
TLV522	VSSOP (8)	3.00mm×3.00mm

(1) 提供されているすべてのパッケージについては、巻末の注文情報を参照してください。

NanoPower酸素センサ・アンプ



英語版のTI製品についての情報を翻訳したこの資料は、製品の概要を確認する目的で便宜的に提供しているものです。該当する正式な英語版の最新情報は、www.ti.comで閲覧でき、その内容が常に優先されます。TIでは翻訳の正確性および妥当性につきましては一切保証いたしません。実際の設計などの前には、必ず最新版の英語版をご参照くださいますようお願いいたします。

目次


1 特長 ... 1
2 アプリケーション ... 1
3 概要 ... 1
4 改訂履歴 ... 2
5 Pin Configuration and Functions ... 2
6 Specifications ... 3
6.1 Absolute Maximum Ratings ... 3
6.2 ESD Ratings ... 3
6.3 Recommended Operating Ratings ... 3
6.4 Thermal Information ... 3
6.5 Electrical Characteristics ... 4
6.6 Typical Characteristics ... 5
7 Detailed Description ... 9
7.1 Overview ... 9
7.2 Functional Block Diagram ... 9
7.3 Feature Description ... 9
7.4 Device Functional Modes ... 9
8 Application and Implementation ... 12
8.1 Application Information ... 12
8.2 Typical Application: 60 Hz Twin "T" Notch Filter ... 12
8.3 Do's and Don'ts ... 13
9 Power Supply Recommendations ... 14
10 Layout ... 14
10.1 Layout Guidelines ... 14
10.2 Layout Example ... 14
11 デバイスおよびドキュメントのサポート ... 15
11.1 デバイス・サポート ... 15
11.2 ドキュメントのサポート ... 15
11.3 コミュニティ・リソース ... 15
11.4 商標 ... 15
11.5 静電気放電に関する注意事項 ... 15
11.6 Glossary ... 15
12 メカニカル、パッケージ、および注文情報 ... 16

4 改訂履歴

日付	改訂内容	注
2016年5月	*	初版

5 Pin Configuration and Functions

8-Pin VSSOP
DGK Package
Top View



Pin Functions

PIN		I/O	DESCRIPTION
PIN	NAME		
1	OUT A	O	Channel A Output
2	–IN A	I	Channel A Inverting Input
3	+IN A	I	Channel A Non-Inverting Input
4	V–	P	Negative (lowest) power supply
5	+IN B	I	Channel B Non-Inverting Input
6	–IN B	I	Channel B Inverting Input
7	OUT B	O	Channel B Output
8	V+	P	Positive (highest) power supply

Copyright © 2016, Texas Instruments Incorporated

6 Specifications

6.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)(1)(2)(3)

		MIN	MAX	UNIT
Supply voltage, V+ to V–		-0.3	6	V
Signal input pins	Voltage(2)	V^- – 0.3	V^+ + 0.3	V
	Current(2)	–10	10	mA
Output short current		Continuous(4)		
Junction temperature		–40	150	°C
Storage temperature, T_{stg}		–65	150	°C

(1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
(2) Input pins are diode-clamped to the power-supply rails. Input signals that can swing more than 0.3 V beyond the supply rails should be current-limited to 10 mA or less.
(3) If Military/Aerospace specified devices are required, please contact the Texas Instruments Sales Office/Distributors for availability and specifications.
(4) Short-circuit to V–.

6.2 ESD Ratings

			VALUE	UNIT
$V_{(ESD)}$	Electrostatic discharge	Human body model (HBM), per ANSI/ESDA/JEDEC JS-001, all pins(1)	±2000	V
		Charged device model (CDM), per JEDEC specification JESD22-C101, all pins(2)	±250	

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.
(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

6.3 Recommended Operating Ratings

over operating free-air temperature range (unless otherwise noted)

	MIN	NOM	MAX	UNIT
Supply Voltage (V^+ – V^-)	1.7		5.5	V
Specified Temperature	–40		125	°C

6.4 Thermal Information

THERMAL METRIC(1)		TLV522 DGK (VSSOP) 8 PINS	UNIT
$R_{\theta JA}$	Junction-to-ambient thermal resistance	182.5	°C/W
$R_{\theta JC(top)}$	Junction-to-case (top) thermal resistance	73.6	
$R_{\theta JB}$	Junction-to-board thermal resistance	104.1	
ψ_{JT}	Junction-to-top characterization parameter	13.7	
ψ_{JB}	Junction-to-board characterization parameter	102.5	
$R_{\theta JC(bot)}$	Junction-to-case (bottom) thermal resistance	N/A	

(1) For more information about traditional and new thermal metrics, see the IC Package Thermal Metrics application report, SPRA953.

Copyright © 2016, Texas Instruments Incorporated

6.5 Electrical Characteristics

T_A = 25°C, V^+ = 3.3 V, V^- = 0 V, V_{CM} = V_O = V^+/2, and R_L > 1 MΩ , unless otherwise noted.


PARAMETER	TEST CONDITIONS	MIN	TYP(1)	MAX	UNIT
OFFSET VOLTAGE					
Input offset voltage (V_{OS})	V_{CM} = 0.3 V	–4	±1	4	mV
	V_{CM} = 3 V	–4	±1	4	
Drift (dV_{OS}/dT)			1.5		µV/°C
Power-Supply Rejection Ratio (PSRR)	V^+ = 1.8 V to 3.3 V, V_{CM} = 0.3 V	80	109		dB
INPUT VOLTAGE RANGE					
Common-Mode voltage range (V_{CM})	CMRR ≥ 62 dB	0		3.3	V
Common-Mode Rejection Ratio (CMRR)	0 V < V_{CM} < 3.3 V	62	90		dB
	0 V < V_{CM} < 2.2V		90		
INPUT BIAS CURRENT					
Input bias current (I_{BIAS})			±1		pA
Input offset current (I_{OS})			±0.1		
INPUT IMPEDANCE					
Differential			10^{13} || 2.5		Ω || pF
Common mode			10^{13} || 2.5		
NOISE					
Input voltage noise density, f = 1 kHz (e_n)			300		nV/√Hz
Current noise density, f = 1 kHz (i_n)			65		fA√Hz
OPEN-LOOP GAIN					
Open-loop voltage gain (A_{OL})	V^+ = 5 V R_L = 100 kΩ to V^+/2, 0.5 V < V_O < 4.5 V	91	101		dB
OUTPUT					
Voltage output swing from positive rail	V^+ = 1.8 V, R_L = 100 kΩ to V^+/2		3	20	mV
Voltage output swing from negative rail	V^+ = 1.8 V, R_L = 100 kΩ to V^+/2		2	20	
Output current sourcing	Sourcing, V^+ = 1.8 V V_O to V^-, V_{IN}(diff) = 100 mV	1	3		mA
Output current sinking	Sinking, V^+ = 1.8 V V_O to V^+, V_{IN}(diff) = –100 mV	1	5		
FREQUENCY RESPONSE					
Gain-bandwidth product (GBWP)	C_L = 20 pF		8		kHz
Slew rate (SR)	G = +1, Rising edge, 1V_{p-p}, C_L = 20 pF		3.6		V/ms
	G = +1, Falling edge, 1V_{p-p}, C_L = 20 pF		3.7		
POWER SUPPLY					
Quiescent current per channel (I_Q)	V_{CM} = 0.3 V, I_O = 0		500	800	nA

(1) Refer to *Typical Characteristics*.

Copyright © 2016, Texas Instruments Incorporated


6.6 Typical Characteristics

T_A = 25 °C, V_{OUT} = V_{CM} = V_S/2, R_{LOAD} = 1 MΩ connected to V_S/2, and C_L = 20 pF, unless otherwise noted.




No Output Load V_{CM} = 0.3 V

Figure 1. Supply Voltage vs Supply Current per Channel, Low Vcm




No Output Load V_{CM} = (V+) – 0.3 V

Figure 2. Supply Voltage vs Supply Current per Channel, High Vcm




No Output Load

Figure 3. Supply Current vs Common Mode at 3.3 V




V_S = 3.3 V

Figure 4. Output Sinking Current vs Output Swing at 3.3 V



V_S = 3.3 V

Figure 5. Output Sourcing Current vs Output Swing at 3.3 V




Output set high (sourcing), shorted to V–

Figure 6. Output Short Circuit Current to V- vs Supply Voltage

Copyright © 2016, Texas Instruments Incorporated


Typical Characteristics (continued)

T_A = 25 °C, V_{OUT} = V_{CM} = V_S/2, R_{LOAD} = 1 MΩ connected to V_S/2, and C_L = 20 pF, unless otherwise noted.




Ouput set low (sinking), shorted to V+

Figure 7. Output Short Circuit Current to V+ vs Supply Voltage




V_S = 3.3 V T_A = 25°C

Figure 8. Input Bias Current vs Common Mode Voltage at 3.3 V




V_S = 3.3 V T_A = 85°C

Figure 9. Input Bias Current vs Common Mode Voltage at 3.3 V




V_S = 3.3 V T_A = 125°C

Figure 10. Input Bias Current vs Common Mode Voltage at 3.3 V



V_S = 5 V R_L = 100 kΩ C_L = 20 pF

Figure 11. Input Referred Voltage Noise




V_S = ±0.9 V R_L = 10 MΩ C_L = 20 pF
G = +1 V_{IN} = ±100 mV

Figure 12. Pulse Response, 200mVpp at 1.8 V

Copyright © 2016, Texas Instruments Incorporated


Typical Characteristics (continued)

T_A = 25 °C, V_{OUT} = V_{CM} = V_S/2, R_{LOAD} = 1 MΩ connected to V_S/2, and C_L = 20 pF, unless otherwise noted.




V_S = ±0.9 V R_L = 10 MΩ C_L = 20 pF
G = +1 V_{IN} = ±500mV

Figure 13. Pulse Response, 1Vpp at 1.8V




V_S = ±2.5 V R_L = 10 MΩ C_L = 20 pF
G = +1 V_{IN} = ±100 mV

Figure 14. Pulse Response, 200mVpp at 5V




V_S = ±2.5 V R_L = 10 MΩ C_L = 20 pF
G = +1 V_{IN} = ±1V

Figure 15. Pulse Response, 2Vpp at 5V




V_S = 1.8 V R_L = 100 kΩ C_L = 20 pF

Figure 16. Gain and Phase vs Temperature at 1.8 V



V_S = 5 V R_L = 100 kΩ C_L = 20 pF

Figure 17. Gain and Phase vs Temperature at 5 V




V_S = 1.8 V R_L = 1 MΩ C_L = 20 pF

Figure 18. Gain and Phase vs Temperature at 1.8 V

Copyright © 2016, Texas Instruments Incorporated


Typical Characteristics (continued)

T_A = 25 °C, V_{OUT} = V_{CM} = V_S/2, R_{LOAD} = 1 MΩ connected to V_S/2, and C_L = 20 pF, unless otherwise noted.




V_S = 5 V R_L = 1 MΩ C_L = 20 pF

Figure 19. Gain and Phase vs Temperature at 5 V



V_S = 1.8 V R_L = 10 MΩ C_L = 20 pF

Figure 20. Gain and Phase vs Temperature at 1.8 V



V_S = 5 V R_L = 10 MΩ C_L = 20 pF

Figure 21. Gain and Phase vs Temperature at 5 V

Copyright © 2016, Texas Instruments Incorporated


7 Detailed Description

7.1 Overview

The TLV522 dual op amplifier is unity-gain stable and can operate on a single supply, making it highly versatile and easy to use.

The TLV522 is fully specified and tested from 1.7 V to 5.5 V. Parameters that vary significantly with operating voltages or temperature are shown in the *Typical Characteristics* curves.

7.2 Functional Block Diagram



7.3 Feature Description

The amplifier's differential inputs consist of a non-inverting input (IN+) and an inverting input (IN–). The device amplifies only the difference in voltage between the two inputs, which is called the differential input voltage. The output voltage of the op-amp V_{OUT} is given by Equation 1:

$$V_{OUT} = A_{OL} (IN^+ – IN^–) \quad (1)$$

where A_{OL} is the open-loop gain of the amplifier, typically around 100 dB.

7.4 Device Functional Modes

7.4.1 Rail-To-Rail Input

The input common-mode voltage range of the TLV522 extends to the supply rails. This is achieved with a complementary input stage — an N-channel input differential pair in parallel with a P-channel differential pair. The N-channel pair is active for input voltages close to the positive rail, typically (V+) – 800 mV to 200 mV above the positive supply, while the P-channel pair is on for inputs from 300 mV below the negative supply to approximately (V+) – 800 mV. There is a small transition region, typically (V+) – 1.2 V to (V+) – 0.8 V, in which both pairs are on. This 400 mV transition region can vary 200 mV with process variation. Within the 400 mV transition region PSRR, CMRR, offset voltage, offset drift, and THD may be degraded compared to operation outside this region.

7.4.2 Supply Current Changes Over Common Mode

Because of the ultra-low supply current, changes in common mode voltages will cause a noticeable change in the supply current as the input stages transition through the transition region, as shown in Figure 22 below.

Copyright © 2016, Texas Instruments Incorporated

Device Functional Modes (continued)




Figure 22. Supply Current Change Over Common Mode at 5 V

For the lowest supply current operation, keep the input common mode range between V- and 1 V below V+.

7.4.3 Design Optimization With Rail-To-Rail Input

In most applications, operation is within the range of only one differential pair. However, some applications can subject the amplifier to a common-mode signal in the transition region. Under this condition, the inherent mismatch between the two differential pairs may lead to degradation of the CMRR and THD. The unity-gain buffer configuration is the most problematic as it will traverse through the transition region if a sufficiently wide input swing is required.

7.4.4 Design Optimization for Nanopower Operation

When designing for ultra-low power, choose system components carefully. To minimize current consumption, select large-value resistors. Any resistors will react with stray capacitance in the circuit and the input capacitance of the operational amplifier. These parasitic RC combinations can affect the stability of the overall system. A feedback capacitor may be required to assure stability and limit overshoot or gain peaking.

When possible, use AC coupling and AC feedback to reduce static current draw through the feedback elements. Use film or ceramic capacitors since large electolytics may have static leakage currents in the tens to hundreds of nanoamps.

7.4.5 Common-Mode Rejection

The CMRR for the TLV522 is specified in two ways so the best match for a given application may be used. First, the CMRR of the device in the common-mode range below the transition region (V_{CM} < (V+) – 1.1 V) is given. This specification is the best indicator of the capability of the device when the application requires use of one of the differential input pairs. Second, the CMRR at V_S = 3.3 V over the entire common-mode range is specified.

7.4.6 Output Stage

The TLV522 output voltage swings 3 mV from rails at 3.3 V supply, which provides the maximum possible dynamic range at the output. This is particularly important when operating on low supply voltages.

The TLV522 Maximum Output Voltage Swing defines the maximum swing possible under a particular output load.

7.4.7 Driving Capacitive Load

The TLV522 is internally compensated for stable unity gain operation, with a 8 kHz typical gain bandwidth. However, the unity gain follower is the most sensitive configuration to capacitive load. The combination of a capacitive load placed directly on the output of an amplifier along with the amplifier's output impedance creates a phase lag, which reduces the phase margin of the amplifier. If the phase margin is significantly reduced, the response will be under damped which causes peaking in the transfer and, when there is too much peaking, the op amp might start oscillating.

Copyright © 2016, Texas Instruments Incorporated

Device Functional Modes (continued)

In order to drive heavy (>50pF) capacitive loads, an isolation resistor, R_{ISO}, should be used, as shown in Figure 23. By using this isolation resistor, the capacitive load is isolated from the amplifier's output. The larger the value of R_{ISO}, the more stable the amplifier will be. If the value of R_{ISO} is sufficiently large, the feedback loop will be stable, independent of the value of C_L. However, larger values of R_{ISO} result in reduced output swing and reduced output current drive.




Figure 23. Resistive Isolation of Capacitive Load

Copyright © 2016, Texas Instruments Incorporated

8 Application and Implementation

NOTE

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

8.1 Application Information

The TLV522 is a ultra-low power operational amplifier that provides 8 kHz bandwidth with only 490 nA quiescent current, and near precision offset and drift specifications at a low cost. These rail-to-rail input and output amplifiers are specifically designed for battery-powered applications. The input common-mode voltage range extends to the power-supply rails and the output swings to within millivolts of the rails, maintaining a wide dynamic range.

8.2 Typical Application: 60 Hz Twin "T" Notch Filter




Figure 24. 60 Hz Notch Filter

8.2.1 Design Requirements

Small signals from transducers in remote and distributed sensing applications commonly suffer strong 60 Hz interference from AC power lines. The circuit of Figure 24 notches out the 60 Hz and provides a gain A_V = 2 for the sensor signal represented by a 1 kHz sine wave. Similar stages may be cascaded to remove 2nd and 3rd harmonics of 60 Hz. Thanks to the nA power consumption of the TLV522, even 5 such circuits can run for 9.5 years from a small CR2032 lithium cell. These batteries have a nominal voltage of 3 V and an end of life voltage of 2 V. With an operating voltage from 1.7 V to 5.5 V the TLV522 can function over this voltage range.

8.2.2 Detailed Design Procedure

The notch frequency is set by:

$$F_0 = 1 / 2\pi RC. \quad (2)$$

To achieve a 60 Hz notch use R = 10 MΩ and C = 270 pF. If eliminating 50 Hz noise, which is common in European systems, use R = 11.8 MΩ and C = 270 pF.

The Twin T Notch Filter works by having two separate paths from V_{IN} to the amplifier's input. A low frequency path through the series input resistors and another separate high frequency path through the series input capacitors. However, at frequencies around the notch frequency, the two paths have opposing phase angles and the two signals will tend to cancel at the amplifier's input.

Copyright © 2016, Texas Instruments Incorporated

Typical Application: 60 Hz Twin "T" Notch Filter (continued)

To ensure that the target center frequency is achieved and to maximize the notch depth (Q factor) the filter needs to be as balanced as possible. To obtain circuit balance, while overcoming limitations of available standard resistor and capacitor values, use passives in parallel to achieve the 2C and R/2 circuit requirements for the filter components that connect to ground.

To make sure passive component values stay as expected clean board with alcohol, rinse with deionized water, and air dry. Make sure board remains in a relatively low humidity environment to minimize moisture which may increase the conductivity of board components. Also large resistors come with considerable parasitic stray capacitance which effects can be reduced by cutting out the ground plane below components of concern.

Large resistors are used in the feedback network to minimize battery drain. When designing with large resistors, resistor thermal noise, op amp current noise, as well as op amp voltage noise, must be considered in the noise analysis of the circuit. The noise analysis for the circuit in Figure 24 can be done over a bandwidth of 2 kHz, which takes the conservative approach of overestimating the bandwidth (TLV522 typical GBW/A_V is lower). The total noise at the output is approximately 800 µVpp, which is excellent considering the total consumption of the circuit is only 900 nA. The dominant noise terms are op amp voltage noise , current noise through the feedback network (430 µVpp), and current noise through the notch filter network (280 µVpp). Thus the total circuit's noise is below 1/2 LSB of a 10-bit system with a 2 V reference, which is 1 mV.

8.2.3 Application Curve




Figure 25. 60 Hz Notch Filter Waveform

8.3 Do's and Don'ts

Do properly bypass the power supplies.

Do add series resistance to the output when driving capacitive loads, particularly cables, MUX and ADC inputs.

Do add series current limiting resistors and external schottky clamp diodes if input voltage is expected to exceed the supplies. Limit the current to 1 mA or less (1 KΩ per volt).

Copyright © 2016, Texas Instruments Incorporated

9 Power Supply Recommendations

The TLV522 is specified for operation from 1.7 V to 5.5 V (±0.85 V to ±2.75 V) over a –40°C to 125°C temperature range. Parameters that can exhibit significant variance with regard to operating voltage or temperature are presented in the *Typical Characteristics*.

CAUTION

Supply voltages larger than 6 V can permanently damage the device.

For proper operation, the power supplies must be properly decoupled. For decoupling the supply lines it is suggested that 10 nF capacitors be placed as close as possible to the operational amplifier power supply pins. For single supply, place a capacitor between V^+ and V^- supply leads. For dual supplies, place one capacitor between V^+ and ground, and one capacitor between V^- and ground.

If your application expects signals above (> 1 kHz) we recommend you use extra supply filtering.

Extra filtering on the power supply input is recommended when presence of signals with frequency above one kHz (> 1 kHz) on the line is expected. Example of such signal sources are high-frequency switching supplies.

10 Layout

10.1 Layout Guidelines

The V+ pin should be bypassed to ground with a low ESR capacitor.

The optimum placement is closest to the V+ and ground pins.

Care should be taken to minimize the loop area formed by the bypass capacitor connection between V+ and ground.

The ground pin should be connected to the PCB ground plane at the pin of the device.

The feedback components should be placed as close to the device as possible to minimize strays.

There is an internal electrical connection between the exposed Die Attach Pad (DAP) and the V^- pin. For best performance the DAP should be connected to the exact same potential as the V^- pin. Do not use the DAP as the primary V^- supply. Floating the DAP pad is not recommended. The DAP and V^- pin should be joined directly as shown in the *Layout Example*.

10.2 Layout Example




Figure 26. Layout Example (Top View)

Copyright © 2016, Texas Instruments Incorporated

11 デバイスおよびドキュメントのサポート

11.1 デバイス・サポート

11.1.1 開発サポート

TINA-TI SPICEベース・アナログ・シミュレータ・プログラム、http://www.ti.com/tool/tina-ti

DIPアダプタ評価モジュール、http://www.ti.com/tool/dip-adapter-evm

TIユニバーサル・オペアンプ評価モジュール、http://www.ti.com/tool/opampevm

TI FilterProフィルタ設計ソフトウェア、http://www.ti.com/tool/filterpro

11.2 ドキュメントのサポート

11.2.1 関連資料

関連資料については、以下を参照してください。

- 『AN-1798 Designing with Electro-Chemical Sensors (電気化学的センサを使用した設計)』、SNOA514
- 『AN-1803 Design Considerations for a Transimpedance Amplifier (トランスインピーダンス・アンプ設計の考慮事項)』、SNOA515
- 『AN-1852 Designing With pH Electrodes (pH電極を使用した設計)』、SNOA529
- 『Compensate Transimpedance Amplifiers Intuitively (トランスインピーダンス・アンプの直感的な補正)』、SBOA055
- 『Transimpedance Considerations for High-Speed Operational Amplifiers (高速オペアンプのトランスインピーダンスの考慮事項)』、SBOA112
- 『Noise Analysis of FET Transimpedance Amplifiers (FETトランスインピーダンス・アンプのノイズ解析)』、SBOA060
- 『Circuit Board Layout Techniques (基板のレイアウト技法)』、SLOA089
- 『Handbook of Operational Amplifier Applications (オペアンプ・アプリケーション・ハンドブック)』、SBOA092

11.3 コミュニティ・リソース

The following links connect to TI community resources. Linked contents are provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's Terms of Use.

TI E2E™ Online Community ***TI's Engineer-to-Engineer (E2E) Community.*** Created to foster collaboration among engineers. At e2e.ti.com, you can ask questions, share knowledge, explore ideas and help solve problems with fellow engineers.

Design Support ***TI's Design Support*** Quickly find helpful E2E forums along with design support tools and contact information for technical support.

11.4 商標

E2E is a trademark of Texas Instruments.
All other trademarks are the property of their respective owners.

11.5 静電気放電に関する注意事項



これらのデバイスは、限定的なESD（静電破壊）保護機能を内 蔵しています。保存時または取り扱い時は、MOSゲートに対す る静電破壊を防止するために、リード線同士をショートさせて おくか、デバイスを導電フォームに入れる必要があります。

11.6 Glossary

SLYZ022 — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

Copyright © 2016, Texas Instruments Incorporated

12 メカニカル、パッケージ、および注文情報

以降のページには、メカニカル、パッケージ、および注文に関する情報が記載されています。これらの情報は、指定のデバイスに対して提供されている最新のデータです。このデータは予告なく変更されることがあり、ドキュメントが改訂される場合もあります。本データシートのブラウザ版を使用されている場合は、画面左側の説明をご覧ください。

Copyright © 2016, Texas Instruments Incorporated

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead finish/ Ball material (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
TLV522DGKR	ACTIVE	VSSOP	DGK	8	2500	RoHS & Green	NIPDAU | SN | NIPDAUAG	Level-2-260C-1 YEAR	-40 to 125	(SL, V522)	Samples
TLV522DGKT	ACTIVE	VSSOP	DGK	8	250	RoHS & Green	NIPDAUAG | SN	Level-1-260C-UNLIM	-40 to 125	SL V522	Samples

(1) The marketing status values are defined as follows:
ACTIVE: Product device recommended for new designs.
LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.
NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.
PREVIEW: Device has been announced but is not in production. Samples may or may not be available.
OBSOLETE: TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".
RoHS Exempt: TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.
Green: TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.


(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


DGK (S–PDSO–G8) PLASTIC SMALL–OUTLINE PACKAGE



4073329/E 05/06

NOTES:
A. All linear dimensions are in millimeters.
B. This drawing is subject to change without notice.
C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 per end.
D. Body width does not include interlead flash. Interlead flash shall not exceed 0.50 per side.
E. Falls within JEDEC MO–187 variation AA, except interlead flash.

DGK (S–PDSO–G8) PLASTIC SMALL OUTLINE PACKAGE



NOTES:
A. All linear dimensions are in millimeters.
B. This drawing is subject to change without notice.
C. Publication IPC–7351 is recommended for alternate designs.
D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC–7525 for other stencil recommendations.
E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

重要なお知らせと免責事項

TI は、技術データと信頼性データ (データシートを含みます)、設計リソース (リファレンス· デザインを含みます)、アプリケーションや設計に関する各種アドバイス、Web ツール、安全性情報、その他のリソースを、欠陥が存在する可能性のある「現状のまま」提供しており、商品性および特定目的に対する適合性の黙示保証、第三者の知的財産権の非侵害保証を含むいかなる保証も、明示的または黙示的にかかわらず拒否します。

これらのリソースは、TI 製品を使用する設計の経験を積んだ開発者への提供を意図したものです。(1) お客様のアプリケーションに適した TI 製品の選定、(2) お客様のアプリケーションの設計、検証、試験、(3) お客様のアプリケーションに該当する各種規格や、その他のあらゆる安全性、セキュリティ、規制、または他の要件への確実な適合に関する責任を、お客様のみが単独で負うものとします。

上記の各種リソースは、予告なく変更される可能性があります。これらのリソースは、リソースで説明されている TI 製品を使用するアプリケーションの開発の目的でのみ、TI はその使用をお客様に許諾します。これらのリソースに関して、他の目的で複製することや掲載することは禁止されています。TI や第三者の知的財産権のライセンスが付与されている訳ではありません。お客様は、これらのリソースを自身で使用した結果発生するあらゆる申し立て、損害、費用、損失、責任について、TI およびその代理人を完全に補償するものとし、TI は一切の責任を拒否します。

TI の製品は、TI の販売条件、または ti.com やかかる TI 製品の関連資料などのいずれかを通じて提供する適用可能な条項の下で提供されています。TI がこれらのリソースを提供することは、適用される TI の保証または他の保証の放棄の拡大や変更を意味するものではありません。

お客様がいかなる追加条項または代替条項を提案した場合でも、TI はそれらに異議を唱え、拒否します。

郵送先住所：Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2024, Texas Instruments Incorporated