

Bullitary



A NEWSLETTER FOR TEXAS INSTRUMENTS MILITARY CUSTOMERS

Volume 14 October 2000 Issue 2
SGYN138

TI Military Logic Deepens Its Bench

(with the addition of the FCT functions and CD4000 products)

TI Enters the FCT Market

With the completion of the acquisition of Cypress Semiconductor's FCT logic family in February of 2000, TI steps into the FCT world to further expand its logic portfolio and provide customers a one-stop shop for their logic needs. There are a wide range of Military functions available, from the FCT138, 240, 244 and 245 to the FCT373, 374 and 377. These are just a few of the functions production released. Widebus™ parts are a planned CMOS Operation offering.



CD4504—A CMOS Hex Voltage-Level Shifter for TTL-to-CMOS or CMOS-to-CMOS Operation

TI Acquires CD4K Products

In December of 1998, Texas Instruments completed the acquisition of select Harris logic products. These Military logic technologies include:

HCMOS (HC & HCT): 199 Functions Advanced CMOS (AC & ACT): 72 Functions

CD4000: 118 Functions.

With these added families and functions, TI customers can expect to receive the world class service and production support to which they are accustomed.

Time for a Change

The chart below displays the upgrade paths available for military designers via TI's Advanced Logic solutions.



	High Drive	LVT, ALVC
High Speed	Low Noise	ALVC, LVT, LVC
	Low Power	ALVC, LVT, LVC
	High Oggand	LVT, ALVC
High Drive	High Speed	
High Drive	Low Noise	LVT
	Low Power	LVT
	High Speed	ALVC, LVT, LVC, LV
Low Noise	High Drive	LVT
	Low Power	ALVC, LVT, LVC, LV, AHC
	High Speed	LVT, ALVC
Low Power	High Drive	ALVC, LVT, LVC
	Low Noise	ALVC, LVT, LVC

New and Future Product Releases

The following chart contains the latest device releases plus some releases planned for 2001.

Parent Device	DSCC #s	Device Function	Packages Available	# of Pins
SNJ54ABT162601	5962-9859301QXA	18-Bit Universal Bus Transceivers with 3-State Outputs	WD	56
SNJ54ABTH245	5962-9762301Q2A/QRA/QSA	Octal Bus Transceivers with 3-State Outputs	J,W,FK	20,20,20
		·	WD	
SNJ54ABTH16244	5962-9762401QXA	16-Bit Buffers/Drivers with 3-State Outputs		48
SNJ54ABTH16245	5962-9762501QXA	16-Bit Bus Transceivers with 3-State Outputs	WD	48
SNJ54ACT00	5962-8769901M2A/MCA/MDA	Quadruple 2-Input Positive NAND Gates	J,W,FK	14,14,20
SNJ54ACT14	5962-9218301M2A/MCA/MDA	Hex Schmitt-Trigger Inverters	J,W,FK	14,14,20
SNJ54AHC123A	5962-9860801Q2A/QEA/EFA	Retriggerable Monostable Multivibrators	J,W,FK	16,16,20
SNJ54AHC138	5962-9851601Q2A/QEA/QFA	3-Line to 8-Line Decoders/Demultiplexers	J,W,FK	16,16,20
SNJ54AHC157	5962-9764201/Q2A/QEA/QFA	Quad 2-Line to 1-Line Data Selectors/Multiplexers	J,W,FK	16,16,20
SNJ54AHC273	5962-9853001Q2A/QRA/QSA	Octal D-Type Flip-Flops with Clear	J,W,FK	20,20,20
SNJ54AHCT123A	5962-98616Q2A/QEA/QFA	Retriggerable Monostable Multivibrators	J,W,FK	16,16,20
SNJ54AHCT138	5962-9851701Q2A/QEA/QFA	3-Line to 8-Line Decoders/Demultiplexers	J,W,FK	16,16,20
SNJ54CBT16212A	5962-9852101QXA	24-Bit Bus-Exchange Switch	WD	56
SNJ54CBT16244	5962-9855301QXA	16-Bit Buffers/Drivers with 3-State Outputs	WD	48
SNJ54LVC157A	5962-0050601QXA	Quadruple 2-Line to 1-Line Data Selector/Multiplexer	J,W,FK	16,16,20
SNJ54LVC257A†	*	Quadruple 2-Line to 1-Line Data Selector/Multiplexer w/ 3-State Outputs	J,W,FK	16,16,20
SNJ54LVTH240	5962-9950801Q2A/QRA/QSA	Octal Buffers/Drivers with 3-State Outputs	J,W,FK	20,20,20
SNJ54LVTH373†	*	3.3-V ABT Octal Transparent D-Type Latches w/ 3-State Outputs	J,W,FK	20,20,20
SNJ54LVTH374†	*	3.3-V ABT Octal Edge-Triggered D-Type Flip-Flops w/ 3-State Outputs	J,W,FK	20,20,20
SNJ54LVTH162373	5962-9763801QXA	3.3-V ABT 16-Bit Transparent D-Type Latches w/ 3-State Outputs	WD	48
SNJ54LVTH162374	5962-9854201QXA	3.3-V ABT 16-Bit Edge-Triggered D-Type Flip-Flops w/ 3-State Outputs	WD	48
CY54FCT543T†	*	Octal Registered Transceivers with 3-State Outputs	WD	48
CY54FCT573AT†	*	Octal Transparent D-Type Latches w/ 3-State Outputs	WD	48

^{† 1}Q 2001 Projected Release

Listening To Our Customers

Military Logic continues to provide leading edge technology, competitive prices, short lead times and broad product offerings. We are also committed to long term production support on mature technologies consistent with customer demand.

Data sheets can be obtained from the Texas Instruments Product Information Center or from Tl's Military Semiconductors website at www.ti.com/sc/military. Widebus is a trademark of Texas Instruments.

Product Information Center

North America

Telephone: 972-644-5580 (English)

Fax: 972-480-7800

PIC: www.ti.com/sc/docs/pic/americas.htm
PIC E-mail: sc-infomaster@ti.com

Military Products: www.ti.com/sc/docs/military/welcome.htm
Distributor Listing: www.ti.com/sc/docs/distmenu.htm

Europe

Multilingual Technical Hotline Francais: +33-(0) 1-30 70 11 64

Francais: +33-(0) 1-30 70 11 64 English: +44 (0) 1604 66 33 99 Italiano: +33-(0) 1-30 70 11 67 Deutsch: +49-(0) 8161-80 33 11 E-Mail: epic@ti.com

24 Hour Fax: +33-(0) 1-30 70 10 32

^{*} DSCC SMD available in all new product releases

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third—party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Mailing Address:

Texas Instruments Post Office Box 655303 Dallas, Texas 75265

Copyright © 2002, Texas Instruments Incorporated