PMP11211 REV A Bill of Materials



| Designator | Quantity | Value | PartNumber | Manufacturer | Description | PackageReference |
|------------------|----------|--------|------------------------|---------------------------------|--|--------------------|
| C100, C101, C102 | 3 | 180uF | 450HXG180MEFCSN22X45 F | Rubycon | CAP ALUM 180UF 450V 20% SNAP | Cap 22x25mm |
| C103 | 1 | 0.33uF | B32922C3334M E | EPCOS Inc | CAP, Film, 0.33uF, 630V, +/-20%, TH | B32922_14.5mm |
| C104 | 1 | 1uF | | | CAP FILM 1UF 450VDC RADIAL | 18.00x20.00x13.50m |
| | | | | • | | m |
| C105, C106, | 4 | 2200pF | DE6E3KJ222MN3A | MuRata | CAP, CERM, 2200 pF, 300 V, +/- 20%, E, TH, 2- Leads, Body 9x7mm, Pin | TH, 2- Leads, Body |
| C109, C110 | | · | | | Spacing 7.5mm | 9x7mm, Pin Spacing |
| | | | | | | 7.5mm |
| C107, C108 | 2 | 0.47uF | ECQ-U2A474ML F | Panasonic | CAP, Film, 0.47 µF, 275 V, +/- 20%, TH | Radial 25x8.5x18.5 |
| C111, C127 | 2 | 1uF | | rdk | CAP, CERM, 1 µF, 50 V, +/- 10%, X7R, 1206 | 1206 |
| C112, C117 | 2 | 0.47uF | C0603C474K8RACTU | Kemet | CAP, CERM, 0.47 µF, 10 V, +/- 10%, X7R, 0603 | 0603 |
| C113 | 1 | 1uF | 0805YD105KAT2A | AVX | CAP, CERM, 1uF, 16V, +/-10%, X5R, 0805 | 0805 |
| C114 | 1 | 470pF | | AVX | CAP, CERM, 470 pF, 100 V, +/- 5%, X7R, 0603 | 0603 |
| C115 | 1 | 1000pF | C0603C102J5RACTU | Kemet | CAP, CERM, 1000 pF, 50 V, +/- 5%, X7R, 0603 | 0603 |
| C116 | 1 | 1uF | C0603C105K4PACTU | Kemet | CAP, CERM, 1 µF, 16 V, +/- 10%, X5R, 0603 | 0603 |
| C118 | 1 | 1000pF | CL10C102JB8NNNC S | Samsung Electro-Mechanics | CAP, CERM, 1000 pF, 50 V, +/- 5%, X7R, 0603 | 0603 |
| C119 | 1 | 10uF | GRM31MR61A106KE19L | MuRata | CAP, CERM, 10 µF, 10 V, +/- 10%, X5R, 1206 | 1206 |
| C120 | 1 | 10uF | UVR1V100MDD1TA | Nichicon | CAP, AL, 10uF, 35V, +/-20%, TH | CAPPR2-5x11 |
| C121 | 1 | 22pF | 06035A220JAT2A | AVX | CAP, CERM, 22pF, 50V, +/-5%, C0G/NP0, 0603 | 0603 |
| C122 | 1 | 6800pF | GRM31BR72J682KW01L | MuRata | CAP, CERM, 6800 pF, 630 V, +/- 10%, X7R, 1206 | 1206 |
| C123 | 1 | 150uF | EEU-FR1E151B F | Panasonic | CAP ALUM 150UF 25V 20% RADIAL | 6.3x11.2mm |
| C124 | 1 | 1uF | 08055C105KAT2A | AVX | CAP, CERM, 1uF, 50V, +/-10%, X7R, 0805 | 0805 |
| C199 | 1 | 15pF | 06035A150JAT2A | AVX | CAP, CERM, 15 pF, 50 V, +/- 5%, C0G/NP0, 0603 | 0603 |
| D100, D103 | 2 | 600V | D25XB60-7000 S | Shindengen | Diode, Switching-Bridge, 600 V, 3.5 A, TH | 5S |
| D101 | 1 | 650V | | | DIODE SCHKY SIC 650V 20A TO-220 | TO-220-2 |
| D104 | 1 | 12V | MMSZ4699T1G | ON Semiconductor | Diode, Zener, 12 V, 500 mW, SOD-123 | SOD-123 |
| D105 | 1 | 100V | BAS316,115 | NXP Semiconductor | Diode, Ultrafast, 100 V, 0.25 A, SOD-323 | SOD-323 |
| D106 | 1 | 30V | BAT54HT1G C | ON Semiconductor | Diode, Schottky, 30 V, 0.2 A, SOD-323 | SOD-323 |
| D107 | 1 | 100V | 1N4148W-7-F | Diodes Inc. | Diode, Ultrafast, 100V, 0.15A, SOD-123 | SOD-123 |
| D108 | 1 | 600V | ES1J-TP | Diodes Inc. | DIODE FAST REC 600V 1A DO214AC | SMA |
| D109 | 1 | 600V | MURS160-13-F | Diodes Inc. | Diode, Ultrafast, 600V, 1A, SMB | SMB |
| F100 | 1 | | 0325020.MXP | _ittelfuse | Fuse, 20 A, 60 V, TH | 3AB |
| H26, H27, H28, | 5 | | MAX01NG | Aavid Thermalloy | MAX Clip | Clip |
| H29, H30 | | | | | | |
| HS100, HS101 | 2 | | 782653B04250G | Aavid | HEATSINK VERT MAX CLIP, BLACK, 4.25 INCHES | 4.25 INCH |
| | | | | | | EXTRUDED HEAT |
| | | | | | | SINK |
| J100, J101 | 2 | | 691214310002 V | Nurth Elektronik eiSos | Terminal Block, 2x1, 3.81mm, 24-16 AWG, 10A, 300VAC, TH | 2x1 Terminal Block |
| J102 | 1 | | 703W-00/54 | Qualtek Electronics Corporation | AC Receptacle, 10A 250VAC | 20X50X28.7mm |
| K100 | 1 | | 875B-1CC-F-S-12VDC | SONG CHUAN | Relay, SPDT (1 Form C), 16A, 12 VDC, TH | 21x16mm |
| L100 | 1 | 570uH | | GCI Technologies | Inductor, Toroid, Ferrite, 570uH, 13 A, 0.03 ohm, TH | D63xH35mm |
| L101, L102 | 2 | 5mH | | Wurth Elektronik | Coupled inductor, 5 mH, A, 0.0065 ohm, +/- 50%, TH | 48x27mm |
| L103 | 1 | 220uH | RFS1113-224ME 0 | | Inductor, Shielded, Ferrite, 220 µH, 1 A, 0.281 ohm, TH | D11xL12.3mm |
| Q100, Q101 | 2 | 650V | IPW65R095C7 | nfineon Technologies | MOSFET N-CH 650V 24A TO247 | TO-247 |
| Q104 | 1 | | | | MOSF NPN 400V 1A SOT-223 | SOT-223 |
| R100, R101 | 2 | 330k | | | RES, 330 k, 5%, 1 W, 2512 | 2512 |
| R102, R103 | 2 | 20k | CRCW120620K0JNEA | /ishay-Dale | RES, 20 k, 5%, 0.25 W, 1206 | 1206 |

| Designator | Quantity | Value | PartNumber | Manufacturer | Description | PackageReference |
|------------------|----------|--------|--------------------|-------------------|---|------------------|
| R104, R105, | 6 | 432k | CRCW1206432KFKEA | Vishay-Dale | RES, 432 k, 1%, 0.25 W, 1206 | 1206 |
| R108, R109, | | | | | | |
| R111, R112 | | | | | | |
| R106, R107, R110 | 3 | 0.036 | 1-2176057-4 | TE Connectivity | RES SMD 0.036 OHM 1% 2W 2512 | 2512 |
| R113 | 1 | 10 | TWW10J10RE | Ohmite | RES, 10, 5%, 10 W, TH | 12.5x9mm |
| R114, R117 | 2 | 10 | CRCW060310R0JNEAHP | Vishay-Dale | RES, 10, 5%, 0.25 W, 0603 | 0603 |
| R115 | 1 | 0 | CRCW06030000Z0EA | Vishay-Dale | RES, 0, 5%, 0.1 W, 0603 | 0603 |
| R116 | 1 | 221 | CRCW0603221RFKEA | Vishay-Dale | RES, 221, 1%, 0.1 W, 0603 | 0603 |
| R118, R120 | 2 | 499k | CRCW1206499KFKEA | Vishay-Dale | RES, 499k ohm, 1%, 0.25W, 1206 | 1206 |
| R119, R121 | 2 | 150 | CRCW1206150RJNEA | Vishay-Dale | RES, 150, 5%, 0.25 W, 1206 | 1206 |
| R122 | 1 | 5.90k | CRCW06035K90FKEA | Vishay-Dale | RES, 5.90 k, 1%, 0.1 W, 0603 | 0603 |
| R123 | 1 | 10.5k | CRCW060310K5FKEA | Vishay-Dale | RES, 10.5 k, 1%, 0.1 W, 0603 | 0603 |
| R124 | 1 | 13.3k | CRCW060313K3FKEA | Vishay-Dale | RES, 13.3 k, 1%, 0.1 W, 0603 | 0603 |
| R125, R126 | 2 | 3.3Meg | CRCW12063M30JNEA | Vishay-Dale | RES, 3.3Meg ohm, 5%, 0.25W, 1206 | 1206 |
| R127 | 1 | 49.9k | CRCW060349K9FKEA | Vishay-Dale | RES, 49.9 k, 1%, 0.1 W, 0603 | 0603 |
| R128 | 1 | 475k | CRCW1206475KFKEA | Vishay-Dale | RES, 475k ohm, 1%, 0.25W, 1206 | 1206 |
| R129 | 1 | 17.8k | CRCW060317K8FKEA | Vishay-Dale | RES, 17.8k ohm, 1%, 0.1W, 0603 | 0603 |
| R130 | 1 | 511 | CRCW0603511RFKEA | Vishay-Dale | RES, 511 ohm, 1%, 0.1W, 0603 | 0603 |
| R131, R132 | 2 | 1.2 | CRCW08051R20JNEA | Vishay-Dale | RES, 1.2 ohm, 5%, 0.125W, 0805 | 0805 |
| R135 | 1 | 12k | CRCW120612K0JNEA | Vishay-Dale | RES, 12k ohm, 5%, 0.25W, 1206 | 1206 |
| RV100 | 1 | | S10K275E2 | EPCOS Inc | Varistor 275V RMS 10MM Radial, TH | 10mm Radial |
| TP100 | 1 | Red | 5000 | Keystone | Test Point, Miniature, Red, TH | Red Miniature |
| | | | | | | Testpoint |
| TP102 | 1 | Black | 5001 | Keystone | Test Point, Miniature, Black, TH | Black Miniature |
| | | | | | | Testpoint |
| U100 | 1 | | UCC27511DBVR | Texas Instruments | Single-Channel High-Speed Low-Side Gate Driver (with 4-A Peak Source and 8-A Peak Sink), DBV0006A | DBV0006A |
| U101 | 1 | | UCC28180D | Texas Instruments | 8-PIN CONTINUOUS CONDUCTION MODE (CCM) PFC CONTROLLER, D0008A | D0008A |
| U102 | 1 | | UCC28722DBV | Texas Instruments | Constant-Voltage, Constant-Current Controller With Primary-Side Regulation, BJT Drive, DBV0006A | DBV0006A |
| D102 | 0 | 30V | BAT54HT1G | ON Semiconductor | Diode, Schottky, 30 V, 0.2 A, SOD-323 | SOD-323 |
| L104 | 0 | 300uH | G154021LF | GCI Technologies | Inductor, 300 µH, 7 A, 0.194 ohm, TH | 43x31mm |
| L105 | 0 | 2.54mH | G154016 | GCI Technologies | Inductor, Toroid, Ferrite, 2.54mH, 13 A, 0.091 ohm, TH | D79xH43mm |
| Q102 | 0 | 80V | FMMT620TA | Diodes | TRANS NPN 80V 1.5A SOT23-3 | SOT-23 |
| Q103 | 0 | 20 V | FMMT718TA | Diodes Inc. | Transistor, PNP, 20 V, 1.5 A, SOT-23 | SOT-23 |

IMPORTANT NOTICE FOR TI REFERENCE DESIGNS

Texas Instruments Incorporated ('TI") reference designs are solely intended to assist designers ("Designer(s)") who are developing systems that incorporate TI products. TI has not conducted any testing other than that specifically described in the published documentation for a particular reference design.

Tl's provision of reference designs and any other technical, applications or design advice, quality characterization, reliability data or other information or services does not expand or otherwise alter Tl's applicable published warranties or warranty disclaimers for Tl products, and no additional obligations or liabilities arise from Tl providing such reference designs or other items.

TI reserves the right to make corrections, enhancements, improvements and other changes to its reference designs and other items.

Designer understands and agrees that Designer remains responsible for using its independent analysis, evaluation and judgment in designing Designer's systems and products, and has full and exclusive responsibility to assure the safety of its products and compliance of its products (and of all TI products used in or for such Designer's products) with all applicable regulations, laws and other applicable requirements. Designer represents that, with respect to its applications, it has all the necessary expertise to create and implement safeguards that (1) anticipate dangerous consequences of failures, (2) monitor failures and their consequences, and (3) lessen the likelihood of failures that might cause harm and take appropriate actions. Designer agrees that prior to using or distributing any systems that include TI products, Designer will thoroughly test such systems and the functionality of such TI products as used in such systems. Designer may not use any TI products in life-critical medical equipment unless authorized officers of the parties have executed a special contract specifically governing such use. Life-critical medical equipment is medical equipment where failure of such equipment would cause serious bodily injury or death (e.g., life support, pacemakers, defibrillators, heart pumps, neurostimulators, and implantables). Such equipment includes, without limitation, all medical devices identified by the U.S. Food and Drug Administration as Class III devices and equivalent classifications outside the U.S.

Designers are authorized to use, copy and modify any individual TI reference design only in connection with the development of end products that include the TI product(s) identified in that reference design. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER TI INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT OF TI OR ANY THIRD PARTY IS GRANTED HEREIN, including but not limited to any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services, or a warranty or endorsement thereof. Use of the reference design or other items described above may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

TI REFERENCE DESIGNS AND OTHER ITEMS DESCRIBED ABOVE ARE PROVIDED "AS IS" AND WITH ALL FAULTS. TI DISCLAIMS ALL OTHER WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, REGARDING THE REFERENCE DESIGNS OR USE OF THE REFERENCE DESIGNS, INCLUDING BUT NOT LIMITED TO ACCURACY OR COMPLETENESS, TITLE, ANY EPIDEMIC FAILURE WARRANTY AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

TI SHALL NOT BE LIABLE FOR AND SHALL NOT DEFEND OR INDEMNIFY DESIGNERS AGAINST ANY CLAIM, INCLUDING BUT NOT LIMITED TO ANY INFRINGEMENT CLAIM THAT RELATES TO OR IS BASED ON ANY COMBINATION OF PRODUCTS AS DESCRIBED IN A TI REFERENCE DESIGN OR OTHERWISE. IN NO EVENT SHALL TI BE LIABLE FOR ANY ACTUAL, DIRECT, SPECIAL, COLLATERAL, INDIRECT, PUNITIVE, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES IN CONNECTION WITH OR ARISING OUT OF THE REFERENCE DESIGNS OR USE OF THE REFERENCE DESIGNS, AND REGARDLESS OF WHETHER TI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Tl's standard terms of sale for semiconductor products (http://www.ti.com/sc/docs/stdterms.htm) apply to the sale of packaged integrated circuit products. Additional terms may apply to the use or sale of other types of TI products and services.

Designer will fully indemnify TI and its representatives against any damages, costs, losses, and/or liabilities arising out of Designer's non-compliance with the terms and provisions of this Notice.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265 Copyright © 2016, Texas Instruments Incorporated