



TEXAS INSTRUMENTS, INC.
TSW1405EVM
PCB REV C
GROUND PLANE-LYR 2



TEXAS INSTRUMENTS, INC.
TSW1405EVM
PCB REV C
POWER PLANE-LYR 3



TEXAS INSTRUMENTS, INC.
 TSW1405EVM
 PCB REV C
 SOLDER MASK BOTTOM 4

87654321

UNLESS OTHERWISE SPECIFIED, ALL NOTES ARE APPLICABLE.
NOTES PRECEDED BY AN UNMARKED "□" ARE NOT APPLICABLE.

1. APPLICATION DESIGN MANUFACTURING AND INSPECTION DOCUMENTS.
IPC-2221A & IPC-2222 / DESIGN STANDARD FOR RIGID PRINTED CIRCUIT BOARDS AND RIGID PRINTED BOARD ASSEMBLIES.
IPC-6012B / QUALIFICATION AND PERFORMANCE SPECIFICATION FOR RIGID PRINTED BOARD.
IPC-A-600G / ACCEPTABILITY OF PRINTED BOARDS.

2. HOLE SIZE APPLIES AFTER PLATING. TOLERANCE TO BE +/- .003.

3. REGISTRATION TOLERANCE: ARTWORK +/- .002
ALL HOLE CENTERS +/- .005 FROM DIMENSION DATUM.

4. MINIMUM COPPER WALL THICKNESS SHALL BE .001 INCH.
FOR ALL PLATED THROUGH HOLES. BREAKOUT NOT ALLOWED.

5. PROCESS AND MATERIAL MUST CONFORM TO UL 796. MATERIAL MUST MEET OR EXCEED UL FLAMMABILITY RATING 94V-0.
MATERIAL: □ SINGLE SIDED, □ DOUBLE SIDED, □ MULTI-LAYER (SEE DETAIL "A")
SEE LAYER STACKUP FOR ALL PRE-PREG & CORE THICKNESSES, COPPER OZ AND MATERIAL. FINISHED BOARD THICKNESS: 0.062 +/- .008

6. MANUFACTURE'S UL MARKING, FLAMMABILITY RATING, LOGO AND DATE CODE TO BE PLACED IN SILKSCREEN ON BOTTOM SIDE OF THE BOARD.

7. SOLDERMASK BOTH SIDES USING TAIYO (OR EQUIVALENT).
COLOR=RED (0.001 TO 0.002" THICK OVER METAL).

8. SILKSCREEN □ TOP SIDE, □ BOTH SIDES, USING □ YELLOW □ WHITE NPI LEADFREE.
REGISTRATION TOLERANCE TO BE +/- .005. SNK IS NOT ALLOWED ON EXPOSED PLATED AREA.

9. P.C. BOARD TO BE FREE OF DIRT, OIL, FINGER PRINTS, ETC.

10. BOARD WARPAGE: WARP AND TWIST SHALL NOT EXCEED .007 INCH PER INCH.
MEASURED AT ANY LOCATION OR DIRECTION ON THE BOARD.

11. BOARD MUST BE 100% ELECTRICALLY TESTED TO ENSURE NO SHORTS OR OPEN CIRCUITS AT 20V.

12. ALL INNER LAYER UNCONNECTED PADS SHALL BE REMOVED.

13. □ ALL OUTER LAYERS USING A X.XX mil TRACE WIDTH SHALL BE 50ohms SINGLE ENDED, +/- 5% TOLERANCE.
□ ALL OUTER LAYERS USING A X.XX mil TRACE WIDTH SHALL BE 100ohms SINGLE ENDED, +/- 5% TOLERANCE.
□ ALL INNER LAYERS USING A X.XX mil TRACE WIDTH SHALL BE 50ohms SINGLE ENDED, +/- 5% TOLERANCE.
□ ALL INNER LAYERS USING A X.XX mil TRACE WIDTH SHALL BE 100ohms SINGLE ENDED, +/- 5% TOLERANCE.
□ ALL OUTER LAYERS USING A 6.00 mil TRACE WIDTH AND 5.00 mil SPACING SHALL BE 100 ohms DIFFERENTIAL, +/-10% TOLERANCE.
□ ALL INNER LAYERS USING A X.XX mil TRACE WIDTH AND X.XX mil SPACING SHALL BE 100 ohms DIFFERENTIAL, +/-10% TOLERANCE.

14. MINIMUM COPPER CONDUCTOR WIDTH IS: .MIL.
MINIMUM COPPER SPACING IS: .MIL.

15. SMOBC/IMMERSION GOLD; 3-8 uIN OVER 100-200 uIN NICKEL PLATING.

16. □ ALL THRU HOLE VIAS TO BE PLATED AND FILLED WITH NON-CONDUCTIVE EPOXY.
FILLED VIAS SHALL BE PLATED AFTER FILLING AND COPLANAR.

17. GROUND ETCH TO BOARD EDGE IS INTENTIONAL. DO NOT PULL BACK.

18. NO CHANGES TO ANY ARTWORK ARE PERMITTED WITHOUT WRITTEN AUTHORIZATION.

19. FINISHED BOARD MUST BE RoHS COMPLIANT AND SURVIVE A LEAD FREE ASSEMBLY.
MAXIMUM REFLOW OF 260 DEGREES C (6 PASSES).

20. □ BOARD TO BE PANELIZED FOR ASSEMBLY.

21. HOLE SIZE APPLIES AFTER PLATING. TOLERANCE TO +/- .003/- .010.

22. FILL 10MIL VIAS UNDER BGA (U1) WITH NON CONDUCTIVE MATERIAL.

REVISIONS

DATEAPPROVED

DESCRIPTION

ZONE

LTR

DETAIL "A"

DRILL CHART: TOP to BOTTOM

ALL UNITS ARE IN MILS

FIGURE	SIZE	PLATED	QTY
*	10.0	PLATED	484
*	12.0	PLATED	368
*	13.0	PLATED	165
*	36.0	PLATED	8
*	38.0	PLATED	6
*	55.0	PLATED	4
*	62.0	PLATED	2
*	35.0	NON-PLATED	2
*	40.0	NON-PLATED	2
Y	125.0	NON-PLATED	2
T	156.0	NON-PLATED	2

TEXAS INSTRUMENTS, INC.

12840010

P03 REV C

LAYER 1

TOP

Copper Foil 0.5oz / Plate to 1.0oz min Layer 1

FR-370HR

Pre-preg +/- 0.008" (material)

LAYER 2

FR-370HR

Core X.XXX" 1.0oz / 1.0oz Layer 2 & 3

LAYER 3

FR-370HR

Pre-preg +/- 0.008" (material)

LAYER 4

BOTTOM

Copper Foil 0.5oz / Plate to 1.0oz min Layer 4

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ARE:
FRACTIONS DECIMALS ANGLES
+/- .XX +/- .01 +/-
+/- .XXX +/- .005 +/-

CONTRACT NO.

APPROVALS

DATE

DRAWN L. NGUYEN 04-10-12

ENGR R. PRENTICE

TEXAS INSTRUMENTS INC.

FABRICATION DRAWING

TSW1405EVM

FINISH

SEE NOTES 7, 8, 9

DO NOT SCALE DRAWING

SIZE

CODE

IDENT NO.

DRAWING NO.

REV.

C

SCALE

NONE

SHEET 1 OF 1